

Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Scripting and breakpointing is also part of this process. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Many applications use a mix of several languages in their construction and use. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Different programming languages support different styles of programming (called programming paradigms). Techniques like Code refactoring can enhance readability. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Unreadable code often leads to bugs, inefficiencies, and duplicated code. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. There are many approaches to the Software development process. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation.