

In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Normally the first step in debugging is to attempt to reproduce the problem. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Many applications use a mix of several languages in their construction and use. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. However, readability is more than just programming style. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Use of a static code analysis tool can help detect some possible problems. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Ideally, the programming language best suited for the task at hand will be selected. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). There are many approaches to the Software development process. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Allen Downey, in his book How To Think Like A Computer Scientist, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Many applications use a mix of several languages in their construction and use. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Programs were mostly entered using punched cards or paper tape. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment.