

The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Different programming languages support different styles of programming (called programming paradigms). They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Programs were mostly entered using punched cards or paper tape. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Ideally, the programming language best suited for the task at hand will be selected. There exist a lot of different approaches for each of those tasks. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. It is usually easier to code in "high-level" languages than in "low-level" ones. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. It is very difficult to determine what are the most popular modern programming languages. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory.