

However, readability is more than just programming style. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Unreadable code often leads to bugs, inefficiencies, and duplicated code. It is usually easier to code in "high-level" languages than in "low-level" ones. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. It is usually easier to code in "high-level" languages than in "low-level" ones. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. There are many approaches to the Software development process. Normally the first step in debugging is to attempt to reproduce the problem. Code-breaking algorithms have also existed for centuries. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices.