

The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Scripting and breakpointing is also part of this process. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Programs were mostly entered using punched cards or paper tape. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. It is very difficult to determine what are the most popular modern programming languages. There are many approaches to the Software development process. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Following a consistent programming style often helps readability. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. It is usually easier to code in "high-level" languages than in "low-level" ones.