

Many applications use a mix of several languages in their construction and use. Scripting and breakpointing is also part of this process. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Scripting and breakpointing is also part of this process. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Programming languages are essential for software development. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Programmable devices have existed for centuries. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Programmable devices have existed for centuries. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. However, readability is more than just programming style.