

Programs were mostly entered using punched cards or paper tape. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Unreadable code often leads to bugs, inefficiencies, and duplicated code. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Computer programmers are those who write computer software. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Integrated development environments (IDEs) aim to integrate all such help. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Programs were mostly entered using punched cards or paper tape. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics.