

Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Integrated development environments (IDEs) aim to integrate all such help. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. However, readability is more than just programming style. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Programmable devices have existed for centuries. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Programming languages are essential for software development. Normally the first step in debugging is to attempt to reproduce the problem. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Integrated development environments (IDEs) aim to integrate all such help. Use of a static code analysis tool can help detect some possible problems. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Different programming languages support different styles of programming (called programming paradigms). Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly.