

Different programming languages support different styles of programming (called programming paradigms). Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Techniques like Code refactoring can enhance readability. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Also, specific user environment and usage history can make it difficult to reproduce the problem. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Integrated development environments (IDEs) aim to integrate all such help. Different programming languages support different styles of programming (called programming paradigms). Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Programs were mostly entered using punched cards or paper tape. There exist a lot of different approaches for each of those tasks. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. There are many approaches to the Software development process. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Techniques like Code refactoring can enhance readability. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research.