

Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Programming languages are essential for software development. Programming languages are essential for software development. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. One approach popular for requirements analysis is Use Case analysis. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs.