

Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Computer programmers are those who write computer software. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Computer programmers are those who write computer software. Also, specific user environment and usage history can make it difficult to reproduce the problem. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Techniques like Code refactoring can enhance readability. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. There are many approaches to the Software development process. Scripting and breakpointing is also part of this process. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Also, specific user environment and usage history can make it difficult to reproduce the problem. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. There exist a lot of different approaches for each of those tasks. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances.