

Techniques like Code refactoring can enhance readability. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. However, readability is more than just programming style. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. It is usually easier to code in "high-level" languages than in "low-level" ones. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Normally the first step in debugging is to attempt to reproduce the problem. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Also, specific user environment and usage history can make it difficult to reproduce the problem. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA).