

Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Scripting and breakpointing is also part of this process. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Scripting and breakpointing is also part of this process. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. There exist a lot of different approaches for each of those tasks. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Unreadable code often leads to bugs, inefficiencies, and duplicated code. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Also, specific user environment and usage history can make it difficult to reproduce the problem. Programming languages are essential for software development. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code.