

Normally the first step in debugging is to attempt to reproduce the problem. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Use of a static code analysis tool can help detect some possible problems. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Normally the first step in debugging is to attempt to reproduce the problem. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Normally the first step in debugging is to attempt to reproduce the problem. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Following a consistent programming style often helps readability. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). It is very difficult to determine what are the most popular modern programming languages. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Use of a static code analysis tool can help detect some possible problems. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Integrated development environments (IDEs) aim to integrate all such help. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language.