

As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). It is usually easier to code in "high-level" languages than in "low-level" ones. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Integrated development environments (IDEs) aim to integrate all such help. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Normally the first step in debugging is to attempt to reproduce the problem. Also, specific user environment and usage history can make it difficult to reproduce the problem. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. It is very difficult to determine what are the most popular modern programming languages. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Also, specific user environment and usage history can make it difficult to reproduce the problem. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. It is very difficult to determine what are the most popular modern programming languages. Also, specific user environment and usage history can make it difficult to reproduce the problem. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. It is very difficult to determine what are the most popular modern programming languages.