

Programming languages are essential for software development. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Computer programmers are those who write computer software. It is usually easier to code in "high-level" languages than in "low-level" ones. Programmable devices have existed for centuries. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Different programming languages support different styles of programming (called programming paradigms). There are many approaches to the Software development process. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Integrated development environments (IDEs) aim to integrate all such help. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. There are many approaches to the Software development process. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. One approach popular for requirements analysis is Use Case analysis. It is usually easier to code in "high-level" languages than in "low-level" ones. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Different programming languages support different styles of programming (called programming paradigms). Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Different programming languages support different styles of programming (called programming paradigms).