

Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Use of a static code analysis tool can help detect some possible problems. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Computer programmers are those who write computer software. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Programming languages are essential for software development. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Programs were mostly entered using punched cards or paper tape. Integrated development environments (IDEs) aim to integrate all such help. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). It affects the aspects of quality above, including portability, usability and most importantly maintainability. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Scripting and breakpointing is also part of this process.