

Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Scripting and breakpointing is also part of this process. Code-breaking algorithms have also existed for centuries. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Programming languages are essential for software development. Scripting and breakpointing is also part of this process. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages.