

The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Programs were mostly entered using punched cards or paper tape. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Programmable devices have existed for centuries. Following a consistent programming style often helps readability. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Scripting and breakpointing is also part of this process. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Code-breaking algorithms have also existed for centuries. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Scripting and breakpointing is also part of this process. Different programming languages support different styles of programming (called programming paradigms). Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line.