

In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the *Book of Ingenious Devices*. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Ideally, the programming language best suited for the task at hand will be selected. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Use of a static code analysis tool can help detect some possible problems. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Programmable devices have existed for centuries.