

Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. However, readability is more than just programming style. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. There are many approaches to the Software development process. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Programmable devices have existed for centuries. Ideally, the programming language best suited for the task at hand will be selected. Techniques like Code refactoring can enhance readability. However, readability is more than just programming style. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the *Book of Ingenious Devices*. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. There exist a lot of different approaches for each of those tasks. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Programmable devices have existed for centuries. However, readability is more than just programming style. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation.