

After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. There exist a lot of different approaches for each of those tasks. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Ideally, the programming language best suited for the task at hand will be selected. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. However, readability is more than just programming style. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Techniques like Code refactoring can enhance readability. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Scripting and breakpointing is also part of this process. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Integrated development environments (IDEs) aim to integrate all such help. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Programming languages are essential for software development. Programmable devices have existed for centuries. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly.