

Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Following a consistent programming style often helps readability. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Integrated development environments (IDEs) aim to integrate all such help. Use of a static code analysis tool can help detect some possible problems. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Code-breaking algorithms have also existed for centuries. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Techniques like Code refactoring can enhance readability. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages.