

Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Scripting and breakpointing is also part of this process. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. One approach popular for requirements analysis is Use Case analysis. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Code-breaking algorithms have also existed for centuries. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. It is usually easier to code in "high-level" languages than in "low-level" ones. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. However, readability is more than just programming style. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Computer programmers are those who write computer software. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. There are many approaches to the Software development process. Programs were mostly entered using punched cards or paper tape. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages.