

By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Scripting and breakpointing is also part of this process. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Use of a static code analysis tool can help detect some possible problems. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Integrated development environments (IDEs) aim to integrate all such help. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Normally the first step in debugging is to attempt to reproduce the problem. Following a consistent programming style often helps readability. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Normally the first step in debugging is to attempt to reproduce the problem. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. It affects the aspects of quality above, including portability, usability and most importantly maintainability. There are many approaches to the Software development process. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine.