

Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Following a consistent programming style often helps readability. There are many approaches to the Software development process. Unreadable code often leads to bugs, inefficiencies, and duplicated code. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Programs were mostly entered using punched cards or paper tape. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers.