

Code-breaking algorithms have also existed for centuries. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. There exist a lot of different approaches for each of those tasks. Code-breaking algorithms have also existed for centuries. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Integrated development environments (IDEs) aim to integrate all such help. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Scripting and breakpointing is also part of this process. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Normally the first step in debugging is to attempt to reproduce the problem. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Normally the first step in debugging is to attempt to reproduce the problem.