

Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). However, Charles Babbage had already written his first program for the Analytical Engine in 1837. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Scripting and breakpointing is also part of this process. Code-breaking algorithms have also existed for centuries. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Many applications use a mix of several languages in their construction and use. Integrated development environments (IDEs) aim to integrate all such help. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the *Book of Ingenious Devices*. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment.