

Normally the first step in debugging is to attempt to reproduce the problem. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Whatever the approach to development may be, the final program must satisfy some fundamental properties. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Ideally, the programming language best suited for the task at hand will be selected. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. However, readability is more than just programming style. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications.