

Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. There are many approaches to the Software development process. Code-breaking algorithms have also existed for centuries. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Many applications use a mix of several languages in their construction and use. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the *Book of Ingenious Devices*. Also, specific user environment and usage history can make it difficult to reproduce the problem. Code-breaking algorithms have also existed for centuries. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Also, specific user environment and usage history can make it difficult to reproduce the problem. Techniques like Code refactoring can enhance readability. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute.