

Ideally, the programming language best suited for the task at hand will be selected. There are many approaches to the Software development process. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. There are many approaches to the Software development process. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the *Book of Ingenious Devices*. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Programmable devices have existed for centuries. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Programmable devices have existed for centuries. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation).