

Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Code-breaking algorithms have also existed for centuries. Programming languages are essential for software development. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. There exist a lot of different approaches for each of those tasks. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. Many applications use a mix of several languages in their construction and use. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Code-breaking algorithms have also existed for centuries. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Programs were mostly entered using punched cards or paper tape. Programmable devices have existed for centuries. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Scripting and breakpointing is also part of this process. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. There are many approaches to the Software development process.