

Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Use of a static code analysis tool can help detect some possible problems. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Use of a static code analysis tool can help detect some possible problems. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Programming languages are essential for software development. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). There exist a lot of different approaches for each of those tasks. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Computer programmers are those who write computer software. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics.