

The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. There are many approaches to the Software development process. However, readability is more than just programming style. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Integrated development environments (IDEs) aim to integrate all such help. Different programming languages support different styles of programming (called programming paradigms). While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Also, specific user environment and usage history can make it difficult to reproduce the problem. Use of a static code analysis tool can help detect some possible problems. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. It is usually easier to code in "high-level" languages than in "low-level" ones. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. It is usually easier to code in "high-level" languages than in "low-level" ones. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Following a consistent programming style often helps readability. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. It affects the aspects of quality above, including portability, usability and most importantly maintainability. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form.