

Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Normally the first step in debugging is to attempt to reproduce the problem. Use of a static code analysis tool can help detect some possible problems. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Computer programmers are those who write computer software. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Computer programmers are those who write computer software. There are many approaches to the Software development process. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Ideally, the programming language best suited for the task at hand will be selected. Different programming languages support different styles of programming (called programming paradigms). Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks.