

Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Techniques like Code refactoring can enhance readability. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Use of a static code analysis tool can help detect some possible problems. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Techniques like Code refactoring can enhance readability. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. Normally the first step in debugging is to attempt to reproduce the problem. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. It is usually easier to code in "high-level" languages than in "low-level" ones. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams.