

Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Unreadable code often leads to bugs, inefficiencies, and duplicated code. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Scripting and breakpointing is also part of this process. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Following a consistent programming style often helps readability. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Computer programmers are those who write computer software. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Code-breaking algorithms have also existed for centuries. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear.