

As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Programming languages are essential for software development. However, readability is more than just programming style. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. It affects the aspects of quality above, including portability, usability and most importantly maintainability. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Also, specific user environment and usage history can make it difficult to reproduce the problem. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. However, readability is more than just programming style. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Many applications use a mix of several languages in their construction and use. Following a consistent programming style often helps readability. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Normally the first step in debugging is to attempt to reproduce the problem. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute.