

There exist a lot of different approaches for each of those tasks. However, readability is more than just programming style. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Scripting and breakpointing is also part of this process. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Unreadable code often leads to bugs, inefficiencies, and duplicated code. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Normally the first step in debugging is to attempt to reproduce the problem. Computer programmers are those who write computer software. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Whatever the approach to development may be, the final program must satisfy some fundamental properties. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years.