

The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Different programming languages support different styles of programming (called programming paradigms). For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Normally the first step in debugging is to attempt to reproduce the problem. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Different programming languages support different styles of programming (called programming paradigms). Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Different programming languages support different styles of programming (called programming paradigms). Ideally, the programming language best suited for the task at hand will be selected. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Programming languages are essential for software development. One approach popular for requirements analysis is Use Case analysis. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware.