

However, readability is more than just programming style. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Whatever the approach to development may be, the final program must satisfy some fundamental properties. It is usually easier to code in "high-level" languages than in "low-level" ones. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. There are many approaches to the Software development process. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Integrated development environments (IDEs) aim to integrate all such help. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Following a consistent programming style often helps readability. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. It is usually easier to code in "high-level" languages than in "low-level" ones. There exist a lot of different approaches for each of those tasks. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics.