

After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Use of a static code analysis tool can help detect some possible problems. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Many applications use a mix of several languages in their construction and use. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Whatever the approach to development may be, the final program must satisfy some fundamental properties. There exist a lot of different approaches for each of those tasks. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Code-breaking algorithms have also existed for centuries.