

After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Different programming languages support different styles of programming (called programming paradigms). In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Also, specific user environment and usage history can make it difficult to reproduce the problem. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. There are many approaches to the Software development process. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers.