

Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Unreadable code often leads to bugs, inefficiencies, and duplicated code. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Whatever the approach to development may be, the final program must satisfy some fundamental properties. One approach popular for requirements analysis is Use Case analysis. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Also, specific user environment and usage history can make it difficult to reproduce the problem. Techniques like Code refactoring can enhance readability. Computer programmers are those who write computer software.