

However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Integrated development environments (IDEs) aim to integrate all such help. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Many applications use a mix of several languages in their construction and use. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Different programming languages support different styles of programming (called programming paradigms). By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Following a consistent programming style often helps readability. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. There exist a lot of different approaches for each of those tasks. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA.