

He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Unreadable code often leads to bugs, inefficiencies, and duplicated code. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Scripting and breakpointing is also part of this process. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Normally the first step in debugging is to attempt to reproduce the problem. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Scripting and breakpointing is also part of this process. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Normally the first step in debugging is to attempt to reproduce the problem. It is very difficult to determine what are the most popular modern programming languages. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems.