

The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Different programming languages support different styles of programming (called programming paradigms). High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Programming languages are essential for software development. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). It is usually easier to code in "high-level" languages than in "low-level" ones. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. It affects the aspects of quality above, including portability, usability and most importantly maintainability. However, readability is more than just programming style. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Many applications use a mix of several languages in their construction and use. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code.