

These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Normally the first step in debugging is to attempt to reproduce the problem. It is usually easier to code in "high-level" languages than in "low-level" ones. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. One approach popular for requirements analysis is Use Case analysis. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Normally the first step in debugging is to attempt to reproduce the problem. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Scripting and breakpointing is also part of this process. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Use of a static code analysis tool can help detect some possible problems. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Normally the first step in debugging is to attempt to reproduce the problem. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. However, readability is more than just programming style.