

Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. One approach popular for requirements analysis is Use Case analysis. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Scripting and breakpointing is also part of this process. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Computer programmers are those who write computer software. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Normally the first step in debugging is to attempt to reproduce the problem. It affects the aspects of quality above, including portability, usability and most importantly maintainability. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Unreadable code often leads to bugs, inefficiencies, and duplicated code.