

Techniques like Code refactoring can enhance readability. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Programs were mostly entered using punched cards or paper tape. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. There exist a lot of different approaches for each of those tasks. It is usually easier to code in "high-level" languages than in "low-level" ones. Use of a static code analysis tool can help detect some possible problems. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). There are many approaches to the Software development process. Following a consistent programming style often helps readability. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation).